1100 V-STAR OIL FILTER COVER MODIFICATION

IF YOU HAVE AN OIL FILTER RELOCATION KIT INSTALLED THE MODIFICATION IS A MUST IF YOU WANT TO REUSE THE ORIGINAL OIL FILTER COVER.

BASIC HAND TOOLS IS ALL YOU NEED.

STEP 1:

MEASURE 30mm FROM FRONT, TOP MOUNTING HOLE DOWNWARD. USE AS A GUIDELINE AND CUT AWAY MATERIAL FOLLOWING THE PROFILE OF THE COVER. START WITH A HACK SAW TO REMOVE THE LARGER PORTIONS OF MATERIAL. REMOVE THE REMAINDER OF THE UNWANTED MATERIAL WITH A BENCH GRINDER, ANGLE GRINDER, OR DREMMEL TOOL. STAY JUST SHY OF THE LINE; USE A FILE OR DREMMEL TOOL WITH A DRUM SANDER ATTATCHMENT TO GET YOUR FINISHED PROFILE. BE CAREFUL NOT TO OVERCUT INTO THE CHROME FINISH ON THE FACE OF THE COVER. REFER TO THE PICTURES BELOW.





STEP 2:

GRIND DOWN THE BACKSIDE OF THE COVER TILL IT IS FLUSH WITH THE REST OF THE COVER. YOU DO NOT WANT THE COVER TO INTERFER IN ANY WAY WITH THE REMOTE OIL FILTER COVER. REFER TO THE PICTURES BELOW.



STEP 3: REINSTALL SIDE COVER WITH THE 2 REMAINING MOUNTING HOLES. ENJOY THE NEW GREAT LOOK.





Provided By: Martin Van Der Hoek, aka Hunter